

Some items are subject to freight charges.
 All prices include GST. Plug & lead not supplied on 415 volt machines.
 Specifications & prices are subject to change without notice.

HAFCO METALMASTER BENCH LATHES

AL-60 LATHE 250mm x 500mm

(L148)

FEATURES OF AL-60 LATHE

- Precision ground 'V' Bed
- Heavy duty A-section belt drive
- 550W induction motor with reversing switch
- Power longfeed and thread cutting
- Rear splash tray is standard

* Optional Accessories

125mm 4-Jaw Chuck (L144)

STANDARD AL-60 ACCESSORIES:

125mm 3-jaw chuck, Faceplate, Fixed & travelling steadies, 2 x dead centres, set of change gears, metric & imperial thread cutting & instruction booklet



LATHE STAND

(L143)



LARGE 26mm SPINDLE BORE

ENCLOSED QUICK CHANGE GEARBOX

STAND - \$229 (L266)

AL-54B 280mm x 750mm

(L1542)

FEATURES:

- Precision 'V'-beds are hardened and ground
- Adjustable ball bearing spindle
- Enclosed oil-bath quick change gearbox
- Includes a full set of change gears for metric/Imperial thread cutting
- 1HP 240V motor

AL-54B PRICE INCLUDES:

3-jaw chuck with reverse jaws, 4-jaw chuck, faceplate, steadies, change gears, dead centre, thread-cutting dial, rear splash guard & drip tray, spanners, toolbox, & instruction booklet

OPTIONAL ACCESSORIES


Turning Tool Kits - see Pg36

12mm (L450)



Drill Chuck & Arbors - see Pg46

16mm Keyed x JT3 (C290)



2MT x JT3 (D442A)

3MT x JT3 (D443A)

Live Centres - see Pg37



2MT (C050)

3MT (C052)

SPECIFICATIONS

| MODEL | AL-60 | AL-54B |
|--------------------------|----------------|----------------|
| CODE | L148 | L1542 |
| TOOLS TO SUIT | 12mm | 12mm |
| CENTRE HEIGHT | 125mm | 140mm |
| DISTANCE BETWEEN CENTRES | 550mm | 750mm |
| SWING OVER BED | 250mm | 280mm |
| SWING OVER CROSS-SLIDE | 150mm | 150mm |
| SPINDLE BORE | 20mm | 26mm |
| TAILSTOCK TAPER | 2MT | 2MT |
| SPINDLE SPEED RANGES | 6(125-2000rpm) | 6(125-2000rpm) |
| LEADSCREW | Metric | Metric |
| IMPERIAL THREAD RANGE | 10 - 44TPI | 8-70TPI |
| METRIC THREAD RANGE | 0.4 - 3.0mm | 0.1 - 2.5mm |
| MOTOR | 550W 240V | 750W 240V |
| WEIGHT (kg) | 145kg | 130kg |