

**Some items are subject to freight charges.**  
 All prices include GST. Plug & lead not supplied on 415 volt machines.  
 Specifications & prices are subject to change without notice.

# HAFCO METALMASTER BENCH LATHES



## AL-335 (L183) 300mm x 910mm

### FEATURES:

- Gear drive headstock for quick change of spindle speeds
- Precision 'V'-beds are hardened and ground, incorporating a rigid webbed casting
- Low voltage work light
- Change gears for metric and imperial thread cutting
- Adjustable taper roller bearings support the spindle
- 9 spindle speeds from 75 to 1400rpm
- Inching button is incorporated on the control panel for convenient spindle speed selection
- Enclosed quick-action feed gearbox for thread cutting
- Automatic longitudinal and cross feeds
- D1-4 camlock spindle for quick chuck changes and safe reverse-direction turning. ISO standard
- Removable gap bedway for larger diameter jobs
- Dual calibrated (except for saddle handwheel - imperial)
- Chuck & changes gear guards fitted with micro switches

### AL-335 PRICE INCLUDES:

3-jaw chuck with reverse jaws, 4-jaw chuck, faceplate, fixed & travelling steadies, change gears, dead centre, thread-chasing dial, spanners, stand, toolbox & instruction booklet

**AL-76 PRICE INCLUDES:**  
 3-jaw chuck with reverse jaws, 4-jaw chuck, faceplate, fixed & travelling steadies, change gears, dead centres, thread-chasing dial, spanners, Quick-change toolpost, 2 Axis Easson DRO, Stand, Splashtray, worklight, toolbox & instruction booklet



## AL-76 (L676) 310mm x 910mm

### FEATURES:

- D1-4 camlock spindle for quick chuck changes and safe reverse-direction turning. ISO standard
- Precision 'V'-beds are hardened and ground, incorporating a rigid webbed casting
- Oil quenched hardened spindle has an adjustable taper roller bearings
- 18 spindle speeds, from 65 to 1800rpm
- Quick-change toolpost with 4 tool holders
- 2 Axis Easson Digital Readout fitted
- Chuckguard with microswitch
- Low voltage work light

### SPECIFICATIONS

MODEL	AL-335	AL-76
CODE	L183	L676
TOOLS TO SUIT	12mm	12mm
CENTRE HEIGHT	150mm	155mm
DISTANCE BETWEEN CENTRES	910mm	910mm
SWING OVER BED	300mm	310mm
SWING OVER CROSS-SLIDE	178mm	190mm
SWING OVER GAP	450mm	450mm
SPINDLE NOSE	D1-4	D1-4
SPINDLE BORE	38mm	38mm
TAILSTOCK TAPER	3MT	3MT
SPINDLE SPEED RANGE	9(75-1400rpm)	18(65-1800rpm)
LEADSCREW	Imperial	Metric
IMPERIAL THREAD RANGE	54(4 - 60TPI)	4-56TPI
METRIC THREAD RANGE	36(0.4 - 7mm)	0.4 - 7mm
MOTOR	2HP/240V	2HP/240V
WEIGHT (kg)	550kg	550kg