

Some items are subject to freight charges.
 All prices include GST. Plug & lead not supplied on 415 volt machines.
 Specifications & prices are subject to change without notice.



HEAVY DUTY GEARED HEAD LATHES

CL-120 630 x 3000mm

(L614)

CL-125 630 x 3000mm

(L616)

CL-130 930 x 4000mm

(L618)

FEATURES CL-120, CL-125, CL-130:

- 550mm wide bed
- D1-11 camlock spindle
- 18 spindle speeds
- Multi-disc forward & reverse clutch
- Rapid traverse selection lever on saddle
- V-bed and headstock gears all hardened and ground
- Large 130mm spindle bore (104mm on CL-120)
- Metric, Imperial, module & diametric pitch thread cutting
- Taper turning standard (optional on CL-120)
- Rack & pinion tailstock



CL-120 (L614) shown above

EXTRA FEATURES of CL-128 & CL-135:

- 600mm wide bed
- Power feed top-slide
- Large 130mm spindle bore standard
- Taper turning standard


CL-128 800 x 4000mm

(L621)

CL-135 1100 x 5000mm

(L623)


CL SERIES PRICE INCLUDES:
 3-jaw chuck with reverse jaws, 4-jaw chuck, faceplate, spindle reducing bush, 2 x dead centres, coolant system, fixed & travelling steadies



Power topslide on (CL-128 & CL-135)



Mounting feet, (standard on all models)



Electro magnetic control switch on (CL-128 & CL-135)



Auto engaging saddle support bearing (only on models 4000mm and over)

SPECIFICATIONS

MODEL	CL-120	CL-125	CL-128	CL-130	CL-135
BED WIDTH	550	550mm	600mm	550mm	600mm
SWING OVER BED	630mm	660mm	800mm	930mm	1100mm
SWING OVER GAP	800mm	800mm	1000mm	1100mm	1300mm
SWING OVER CROSS-SLIDE	350mm	350mm	480mm	650mm	800mm
SPINDLE NOSE	D1-11	D1-11	D1-11	D1-11	D1-11
SPINDLE BORE	104mm	130mm	130mm	130mm	130mm
TAILSTOCK TAPER	5MT	5MT	5MT	5MT	5MT
SPINDLE SPEED RANGE	18(7.5-1000rpm)	18(8-880rpm)	18(5.4-720rpm)	18(6-800rpm)	18(4.8-640rpm)
LEADSCREW	Metric	Metric	Metric	Metric	Metric
IMPERIAL THREAD RANGE	26(1-14TPI)	26(1-14TPI)	26(1-14TPI)	26(1-14TPI)	26(1-14TPI)
METRIC THREAD RANGE	50(1-24mm)	50(1-24mm)	50(1-24mm)	50(1-24mm)	50(1-24mm)
MOTOR 415V	11kW (14.5HP)	11kW (14.5HP)	15kW (20HP)	11kW (14.5HP)	15kW (20HP)
STANDARD ACCESSORIES					
4 JAW CHUCK	500mm	500mm	500mm	500mm	500mm
FACE PLATE	650mm	650mm	800mm	930mm	1120mm
FOLLOW REST	20-130	20-130	20-130	30-180	30-180
STEADY REST	20-170	20-170	40-350	30-420	40-460
EXTRA STEADY REST	160-350	160-350	-	-	-

ALL MODELS AVAILABLE IN 3000, 4000, 5000, 6000 - 14,000MM WORKPIECE LENGTH

