

Some items are subject to freight charges.
All prices include GST. Plug & lead not supplied on 415 volt machines.
Specifications & prices are subject to change without notice.

DRILLING MACHINES

SBD-20B

(D138)

SPD-20B

(D140)

SBD-25A

(D144)

SPD-25A

(D147)

PD-22

(D148)

PD-26

(D152)



2MT SPINDLE

SBD-20B



SOLID ONE-PIECE CAST IRON HANDLE

WORK LIGHT INCLUDED ON SBD-25A SPD-25A PD-22 PD-26

SPD-25A



3MT SPINDLE

PD-22



1.5HP/240V MOTOR

PD-26

FEATURES:

- Ideal for workshop and farm use
- Quiet 'V'-belt drive ■ Fan-cooled motor
- Safety magnetic-type switch
- Rack & pinion table height adjustment
- Table tilts to 45° either way and rotates 360°
- Drilling depth stop setting with scale
- Includes drill chuck and arbor
- 12 months warranty

EXTRA FEATURES OF SBD-25A/SPD-25A/PD-22/PD-26

- Worklight standard
- More horsepower for larger drilling capacity
- Heavier quill and column design for more rigidity
- Larger Throat depth and 'V'-belt drive section reduces belt slip during operation and gives wider speed range
- Safety cut out switch on belt guard (SBD-25A/SPD-25A/PD-22)

SPECIFICATIONS

| MODEL | SBD-20B | SPD-20B | SBD-25A | SPD-25A | PD-22 | PD-26 |
|------------------|------------|------------|------------|------------|------------|------------|
| CODE | D138 | D140 | D144 | D147 | D148 | D152 |
| TYPE | Bench | Pedestal | Bench | Pedestal | Pedestal | Pedestal |
| USAGE | Med-Duty | Med-Duty | Hvy-Duty | Hvy-Duty | Hvy-Duty | Hvy-Duty |
| WORKLIGHT | NO | NO | YES | YES | YES | YES |
| DRILL CAP | 16mm | 16mm | 20mm | 20mm | 28mm | 32mm |
| SPINDLE SIZE | No. 2mt | No. 2mt | No. 2mt | No. 2mt | No. 3mt | No. 3mt |
| SPEEDS | 16(M Sect) | 16(M Sect) | 16(A Sect) | 16(A Sect) | 16(A Sect) | 12(A Sect) |
| RANGE (RPM) | (220-3480) | (220-3480) | (195-3645) | (195-3645) | (160-3000) | (110-2880) |
| MOTOR/240V | 1HP | 1HP | 1HP | 1HP | 1HP | 1.5HP |
| DRILL DEPTH | 80mm | 80mm | 80mm | 80mm | 80mm | 120mm |
| QUILL DIA. | 40mm | 40mm | 47mm | 47mm | 47mm | 62mm |
| COLLAR DIA. | 55mm | 55mm | 60mm | 60mm | 60mm | 75mm |
| THROAT DEPTH | 170mm | 170mm | 195mm | 195mm | 215mm | 260mm |
| TABLE TYPE | Round | Round | Round | Round | Square | Square |
| TABLE DIMENSIONS | 300mm | 300mm | 300mm | 300mm | 360 x 360 | 475 x 430 |
| SPINDLE TO BASE | 620mm | 1165mm | 620mm | 1165mm | 1190mm | 1190mm |
| COLUMN DIA. | 70mm | 70mm | 80mm | 80mm | 80mm | 92mm |
| FULL HEIGHT | 1060mm | 1610mm | 1060mm | 1630mm | 1635mm | 1700mm |
| WEIGHT KG | 55 | 58 | 61 | 67 | 85 | 144 |

DRILLING VICES



- 4" (V124)
- 5" (V125)
- 6" (V126)
- 4" (V114) tilting

4" (100mm) (V120)

Travel - 4 1/2" x 4"
Weight - 10 kg

6" (150mm) (V122)

Travel - 8" x 6"
Weight - 17 kg



PIPE NOTCHER ATTACHMENT



(P090)

SUITS MOST CONVENTIONAL DRILLING MACHINES

- Uses standard holesaws
- 2" (50mm) Tube Capacity
- Cuts at angles of up to 45°
- Graduated scale

SEE PAGES 45-47 FOR MORE ACCESSORIES