

Some items are subject to freight charges.

All prices include GST. Plug & lead not supplied on 415 volt machines. Specifications & prices are subject to change without notice.



**PD-35** (D162)

**FEATURES:**

- Ideal for industrial workshop use
- Large spindle diameters and heavy castings
- TEFC 1 HP motor rated for continuous use with overload protection
- 'B'-section belt drive
- Complete with quality drill chuck and heavy duty chuck guard
- Double locking, square tilting/rotating table suitable for suds collection
- Microswitch cut-out on belt guard
- No volt contactor with emergency stop

MODEL	PD-35
CODE	(D162)
TYPE	Pedestal
USAGE	Industrial Duty
DRILL CAP	32mm
SPINDLE SIZE	No. 3MT
SPEEDS	9(B Sect.)
RANGE (RPM)	180-1680
MOTOR/240V (TEFC)	1HP
DRILL DEPTH	125mm
QUILL DIA.	72mm
COLLAR DIA.	92mm
THROAT DEPTH	225mm
TABLE TYPE	Square
SPINDLE TO BASE	1175mm
COLUMN DIA.	92mm
FULL HEIGHT	1700mm
WEIGHT (kg)	136

**T-SLOTTED, TILTING AND ROTATING TABLE**

**GEARED HEAD DRILLS**

**GHD-22**  
**MANUAL FEED MODEL**

(D170)

**FEATURES – GHD22**

- 3MT spindle
- 8 drilling speeds from 105 - 2900rpm 415V
- Helical cut gears for quiet operation
- Rack and pinion wind up table
- Rectangular T-Slotted table
- Heavy duty chuck guard
- Emergency stop button
- Adjustable depth stop



**DMF-40**  
**DRILLING/MILLING**

**415V** (D129)

**240V** (D129A)

**FEATURES – DMF-40**

- 3MT spindle
- 12 drilling speeds from 75-3200rpm 415V Model
- 6 drilling speeds from 75-1500rpm 240V Model
- Micro downfeed adjustment
- Tilting head
- Emergency stop switch and overload protection
- Adjustable accurate depth setting for increased productivity
- Rack and pinion wind-up table
- Adjustable gibs on table
- Includes drawbar for milling
- Tapping function (415V only)

**SPECIFICATIONS**

MODEL	GHD-22	DMF-40
CODE	D170	D129/D129A
SPINDLE	3MT	3MT
DRILLING CAP	25mm	25mm
AUTO FEED	NO	NO
SPEEDS	8	12/6
RPM RANGE	105-2900	75-3200/75-1500
COLUMN DIA	100mm	115mm
DRILL DEPTH	120mm	130mm
QUILL DIA	55mm	75mm
THROAT DEPTH	255mm	250mm
TABLE SIZE	350 x 500	600 x 190
SPINDLE TO TABLE	830mm	610mm
SPINDLE TO BASE	1240mm	1180mm
FULL HEIGHT	1800mm	1950mm
MOTOR	415V 0.75Kw	415V 1.1kW/240V 1.5kW
WEIGHT (kg)	180kg	340kg