

Some items are subject to freight charges.  
All prices include GST. Plug & lead not supplied on 415 volt machines.  
Specifications & prices are subject to change without notice.

# METAL CUTTING BANDSAWS

## BS-7LA (B005)

### FEATURES BS-7LA:

- 7" x 12" rectangular capacity
- Adjustable hydraulic feed cutting rate for various sections
- Includes suds pump for longer blade life
- Angle cuts to 45° using calibrated vice
- Fully adjustable blade roller guides for straight cutting
- 4-speed pulley drive
- Portable – on wheels for ease of use
- Automatic electric cut-out switch
- Heavy-duty 750W/240V fully enclosed fan-cooled motor

45° SWIVEL VICE



## BS-7DS (B008A)

### FEATURES BS-7DS:

- 7" x 12" rectangular capacity
- BS-7DS has ±45° swivel head for easy angle cutting without moving material
- Adjustable hydraulic feed cutting rate for various sections
- Includes suds pump for longer blade life
- Angle cuts to 45° using calibrated vice
- Fully adjustable blade roller guides for straight cutting
- 4-speed pulley drive
- Portable – on wheels for ease of use
- Automatic electric cut-out switch
- Heavy-duty 750W/240V fully enclosed fan-cooled motor

### CAPACITY

|     |      |           |
|-----|------|-----------|
| 45° | ○ mm | 100       |
| 45° | □ mm | 95 x 140  |
| 90° | ○ mm | 175       |
| 90° | □ mm | 180 x 215 |

SWIVEL HEAD ± 45°



## BS-912 (B014)

### FEATURES BS-912:

- Large 9" (230mm) round capacity
- Adjustable hydraulic down feed
- Easily-adjustable blade guides for accurate cutting
- Quick-action swivel vice
- Portable on wheels for convenient positioning
- Cuts to 45° using calibrated vice
- Automatic cut out
- Includes coolant system & length stop

QUICK ACTION VICE

4 SPEEDS – 50-257MPM

PORTABLE ON WHEELS



### BLADE CHART: to suit models BS-7L/A/S

| CODE | TYPE    | TPI   | PRICE ea. | x10 | MATERIAL CAP. GUIDE |
|------|---------|-------|-----------|-----|---------------------|
| B210 | CARBON  | 6     |           |     | From 25 - 50mm      |
| B212 | CARBON  | 8     |           |     | From 13 - 40mm      |
| B214 | CARBON  | 10    |           |     | From 9.5 - 35mm     |
| B216 | CARBON  | 14    |           |     | From 6.4 - 22mm     |
| B400 | BIMETAL | 4-6   |           |     | From 25 - 75mm      |
| B404 | BIMETAL | 6-10  |           |     | From 9.5 - 50mm     |
| B408 | BIMETAL | 10-14 |           |     | From 6.4 - 35mm     |

### BLADE CHART: to suit model BS-912 (BS-9L Blades also available)

| CODE | TYPE    | TPI   | PRICE ea. | x10 | MATERIAL CAP. GUIDE |
|------|---------|-------|-----------|-----|---------------------|
| B220 | CARBON  | 6     |           |     | From 25 - 50mm      |
| B223 | CARBON  | 10    |           |     | From 9.5 - 35mm     |
| B226 | CARBON  | 14    |           |     | From 6.4 - 22mm     |
| B412 | BIMETAL | 4-6   |           |     | From 25 - 75mm      |
| B414 | BIMETAL | 6-10  |           |     | From 9.5 - 50mm     |
| B418 | BIMETAL | 10-14 |           |     | From 6.4 - 35mm     |

### SPECIFICATIONS

| MODEL            | BS-7LA            | BS-7DS            | BS-912        |           |
|------------------|-------------------|-------------------|---------------|-----------|
| CODE             | B005              | B008A             | B014          |           |
| Type/Operation   | Hor. Vert./Manual | Hor. Vert./Manual | Hor./Manual   |           |
| 90°              | Round             | 175               | 175           | 230       |
| Capacity         | Square            | 175 x 175         | 175 x 175     | 230 x 230 |
| in mm            | Rectangle         | 175 x 300         | 180 x 215     | 178 x 305 |
| Blade Speeds/MPM | 21-34-46-60       | 21-34-46-60       | 25-42-62-83   |           |
| Coolant System   | Yes               | Yes               | Yes           |           |
| Motor W/HP/Volts | 750W 1HP 240V     | 750W 1HP 240V     | 750W 1HP 240V |           |
| Nett Weight (kg) | 125kg             | 165kg             | 165kg         |           |

