



# HYDRAULIC GUILLOTINES

**Some items are subject to freight charges.**  
 All prices include GST. Plug & lead not supplied on 415 volt machines.  
 Specifications & prices are subject to change without notice.

**Optional:** Estun NC Programmable Controller and Ball Screw Backgauge



- HG-860 (2500 x 6mm)** (S613)
- HG-1060 (3200 x 6mm)** (S614)
- HG-1360 (4000 x 6mm)** (S615)

**FEATURES:**

- Heavy duty overdriven machine construction
- Deep throat for slitting (250mm)
- Rapid blade clearance adjustment (0.05 - 6mm)
- Individual hydraulic hold downs with nylon pads
- Shadow line lighting
- 800mm motorised backgauge with fine adjustment.  
Swing away backgauge function for cutting long sheets
- 4 edge quality INOX blade suitable for stainless steel
- Rexroth & Bosch hydraulic valves
- Telemecanique electrical components
- Transfer balls on table & squaring arms
- 3 heavy duty squaring arms with 2 flip over material stops
- Stroke counter and short stroke adjustment
- Sliding chute for cut pieces
- Larger models available to 25mm capacity
- Fully guarded back gates with microswitch interlock



**HG-1360 shown**

- HG-1080 (3200 x 8mm)** (S616)
- HG-1012 (3200 x 12mm)** (S617)
- HG-1312 (4000 x 12mm)** (S619)



800mm Motorised Back Gauge



Easy material access for hands



250mm Throat



Blade Clearance Adjustment



Sliding Chute

**SPECIFICATIONS**

MODEL	HG-860	HG-1060	HG-1360	HG-1080	HG-1380	HG-1012	HG-1312
CODE	S613	S614	S615	S616	-	S617	S619
SHEARING THICKNESS(mm)	6	6	6	8	8	12	12
SHEARING LENGTH(mm)	2500	3200	4000	3200	4000	3200	4000
STROKES/(min)	20	18	14	12	10	14	10
BLADE ANGLE	1°30'	1°30'	1°30'	1°30'	1°30'	1°30'	1°30'
BACKGAUGE TRAVEL (mm)	800	800	800	800	800	800	800
DEPTH OF THROAT(mm)	250	250	250	250	250	320	320
MOTOR(kW)	7.5	7.5	7.5	11	11	18.5	18.5
WEIGHT(kg)	6000	6580	8500	7800	9800	10000	15000

