



# HYDRAULIC PRESSBRAKES

**Some items are subject to freight charges.**  
 All prices include GST. Plug & lead not supplied on 415 volt machines.  
 Specifications & prices are subject to change without notice.



- PB-40 (2000mm)** (S618)
- PB-63 (3200mm)** (S622)
- PB-100 (3200mm)** (S625)

- PB-125 (3200mm)** (S626)
- PB-125 (4000mm)** (S630)
- PB-160 (3200mm)** (S629)
- PB-160 (4000mm)** (S632)
- PB-200 (4000mm)** (S634)

**FEATURES:**

- Hydraulic/Mechanical torsion bar design assuring accurate parallelism and repeatability
- Powered backgauge with adjustable height finger stops
- Segmentered top tool with European style wedge clamp adjustment
- Pendant control box including backgauge and depth controls
- German made Siko electronic digital readouts for depth and backgauge position (mechanical gauges on PB-40A)
- Integrated hydraulic system including rapid approach/slow bend, adjustable tonnage control and overload protection
- **Note: Prices do not include guarding**

**Optional: Estun 2-Axis NC Programmable Controller**  
 Ball screw backgauge with linear guideways


**PB-125**



Shut Height Adjustment



Wedge Clamp Adjustment



Adjustable Backgauge Fingers



Motorised Backgauge

**SPECIFICATIONS**

MODEL	PB-40	PB-63	PB-100	PB-125	PB-160	PB-200
CODE	S618	S622	S625	S626/S630	S629/S632	S634
NOMINAL PRESSURE(T)	40	63	100	125	160	200
LENGTH OF WORK TABLE(mm)	2000	3200	3200	3200/4000	3200/4000	4000
DISTANCE BETWEEN COLUMNS(mm)	1650	2670	2650	2650/3150	2640/3100	3200
MAX. OPEN HEIGHT (mm)	335	330	375	375/420	480	510
BACKGAUGE TRAVEL (mm)	600	600	600	600	600	600
THROAT DEPTH (mm)	200	250	320	320	320	320
RAM STROKE(mm)	100	100	150	150	200	200
MOTOR(kW)	3	5.5	7.5	7.5	11	11
WEIGHT(kg)	3100	6050	7200	8200/9000	10800/13000	18500

