

Some items are subject to freight charges.
 All prices include GST. Plug & lead not supplied on 415 volt machines.
 Specifications & prices are subject to change without notice.



HYDRAULIC PLATE ROLLS

HUGE range of models available
Call for SPECIFICATIONS & PRICES

THREE & FOUR ROLL HYDRAULIC PLATE BENDING MACHINES

FEATURES

- This machine is particularly suitable for medium plate and heavy plate for the production of cylinders and varying radiused parts
- Bottom pinching roll with hydraulic positioning (top and down movement)
- Two lateral rolls with double pinch pyramid action (bottom pinching and lateral rolls with balancing system to guarantee perfect parallelism and high quality production)
- Top roll is driven by a hydraulic motor coupled to the planetary gear box (equipped with overload protection system) – lateral side rolls are driven – bottom roll is idle (free)
- Digital displays (3pcs) are provided for locating setting of roll positions
- Hydraulic drop end for ease of cylinder removal
- Steel welded heavy frame construction, thermally stress relieved
- Induction hardened rolls are of high tensile carbon steel forgings, Conical bending device
- Hydraulic elements : Motor and pump group, pressure valves, solenoid valves, oil display and etc Bosch Rexroth or Parker or Duplomatic (Italian) components used
- Electric equipments : Siemens or Telemecanique or NAIS (matsushita Corp)



Made in Turkey



3R HSS 30-320



STANDARD FEATURES



Standard Hydraulic drop end

MODELS	CODE	USEFULL LENGTH	BENDING CAPACITY	ROLL DIAMETER	MOTOR (kW)	DIMENSIONS L x W x H	WEIGHT (kg)
4R HS 25-245	(S776)	2550	8	245	7.5	4500 x 1500 x 1500	6600
* 4R HSS 30-280	(S778)	3050	10	280	15	4500 x 1700 x 1800	10000

* C/W 2 additional DRO's for cone bending, 4M overhead crane & Side lateral support table



SWAGE & JENNY MACHINES

IK-1.2

(S642)

FEATURES

- H/duty Cast iron construction
- 4 set standard rolls



IK-1.2

SPECIFICATIONS

MODEL	IK-1.2	IKMP-1.2	IKMS-2.5	IBKS-40
CODE	S642	S643	S644	S645
BENDING CAPACITY(mm)	1.2	1.2	2.5	4.0
SHAFT TO FRAME(mm)	180	180	410	500
ROLL DIA.(mm)	62	62	96	126
MOTOR / REVS(kW/rpm)	-	0.75/32	1.5/16	2.2/12
WEIGHT(kg)	50	110	380	500



Made in Turkey

IKMP-1.2

(S643)

FEATURES

IKMP-1.2/IKMS-2.5

- H/duty Cast iron construction
- 4 set standard rolls
- Adjustable side support
- Reduction motor with brake
- Roving footpedal control
- Adjustable idle



IKMP-1.2

