

Some items are subject to freight charges.
 All prices include GST. Plug & lead not supplied on 415 volt machines.
 Specifications & prices are subject to change without notice.

HAFCO METALMASTER SHEETMETAL ROLLS

PANBRAKE/FOLDER GUILLOTINE & ROLLS

- CM-300** (S648)
 - CM-760** (S650)
 - CM-1000** (S652)
- CAPACITY:**
 300mm x 1mm capacity (38mm rolls)
 760mm x 1mm capacity (42mm rolls)
 1000mm x 1mm capacity (42mm rolls)

- FEATURES CM-300/CM-760/CM-1000**
- Ideal for light sheetmetal work
 - Cast iron construction
 - Simultaneous operation of all three functions
 - Bender has removable sections on top blade
 - Top roller opens for job removal
 - Weighs 45/120/250kgs



(S652)

CURVING ROLLS

- SRG24 - Bench Model** (S268)
- SRG40** (S270)
- SRG50** (S271)

- FEATURES SRG40/50**
- Cast-iron construction
 - Ground rolls, Top roll lifts out
 - Quick adjustment
 - Includes stand



SPECIFICATIONS

MODEL	SRG24	SRG40	SRG50
CODE	S268	S270	S271
ROLL DIAMETER	24" (610) x 40mm	40" (1000) x 50mm	50" (1270) x 75mm
CAPACITY	1mm	18G 1.2mm	16G 1.6mm
WEIGHT (kg)	38kg	86kg	200kg

BRAMLEY SHEETMETAL

BENCH MOUNTED CURVING ROLLER

- 18" x 22G (450 x 0.8mm)**
- Ideal for tinsmiths, education, general workshop use
 - Solid all steel construction
 - 1" (25mm) diameter rollers
 - Top roller lifts out
 - Std grooves for wiring work
 - Excellent design features



(S517)

PANBRAKE FOLDER

- 24" x 18G (612mm x 1.2mm) Capacity
- Strong steel construction
- Ideal for education, plumbing, electrical applications



(S523)

CURVING ROLLS



- Top roller lifts out **1000** (S273A)
- Quick roller adjustment
- Solid steel construction **1270** (S274)


SPECIFICATIONS

MODEL	1000	1270
CODE	S273A	S274
ROLL DIAMETER	40" (1000) x 50mm	50" (1270) x 63mm
CAPACITY	18G 1.2mm	16G 1.6mm

HAND SHEARS INDUSTRIAL DUTY HS4 HS5

CAPACITIES

MODEL	H.S.4	H.S.5
CODE	S220	S222
Plate	4mm(3/16")	5mm(7/32")
Flat	60mm x 5mm (2 3/8" x 7/32")	70mm x 6mm (2 3/4" x 1/4")
Round	11mm(7/16")	13mm (1/2")
Blade	155mm(6")	200mm
Cut Length	110mm(4 1/4")	160mm



HAND PUNCH

MAX. PUNCH CAP. IN MILD STEEL

Dia.	Thickness
10 x	4mm
8 x	4mm
6 x	3mm
5 x	3mm
4 x	2mm
3 x	1.5mm

- (P114)
 Includes 6 punches & dies
- 10mm in 4mm Plate capacity
 - Throat depth 3" (75mm)
 - Ideal for quick production work
 - Punch & Dies: 3,4,5,6,8 & 10mm

