

**Some items are subject to freight charges.**  
 All prices include GST. Plug & lead not supplied on 415 volt machines.  
 Specifications & prices are subject to change without notice.

# HAFCO METALMASTER SHEETMETAL ROLLS

## PANBRAKE/FOLDER GUILLOTINE & ROLLS

**CM-300**

(S648)

**CM-760**

(S650)

**CM-1000**

(S652)

**CAPACITY:**

300mm x 1mm capacity (38mm rolls)  
 760mm x 1mm capacity (42mm rolls)  
 1000mm x 1mm capacity (42mm rolls)

**FEATURES CM-300/CM-760/CM-1000**

- Ideal for light sheetmetal work
- Cast iron construction
- Simultaneous operation of all three functions
- Bender has removable sections on top blade
- Top roller opens for job removal
- Weighs 45/120/250kgs



(S652)

## CURVING ROLLS

**SRG24 - Bench Model**

(S268)

**SRG40**

(S270)

**SRG50**

(S271)

**FEATURES SRG40/50**

- Cast-iron construction
- Ground rolls, Top roll lifts out
- Quick adjustment
- Includes stand



**SPECIFICATIONS**

MODEL	SRG24	SRG40	SRG50
CODE	S268	S270	S271
ROLL DIAMETER	24" (610) x 40mm	40" (1000) x 50mm	50" (1270) x 75mm
CAPACITY	1mm	18G 1.2mm	16G 1.6mm
WEIGHT (kg)	38kg	86kg	200kg

# BRAMLEY SHEETMETAL

## BENCH MOUNTED CURVING ROLLER

**18" x 22G (450 x 0.8mm)**

- Ideal for tinsmiths, education, general workshop use
- Solid all steel construction
- 1" (25mm) diameter rollers
- Top roller lifts out
- Std grooves for wiring work
- Excellent design features



(S517)

## PANBRAKE FOLDER

- 24" x 18G (612mm x 1.2mm) Capacity
- Strong steel construction
- Ideal for education, plumbing, electrical applications



(S523)

## CURVING ROLLS



- Top roller lifts out **1000** (S273A)
- Quick roller adjustment
- Solid steel construction **1270** (S274)

**SPECIFICATIONS**

MODEL	1000	1270
CODE	S273A	S274
ROLL DIAMETER	40" (1000) x 50mm	50" (1270) x 63mm
CAPACITY	18G 1.2mm	16G 1.6mm

## HAND SHEARS

INDUSTRIAL DUTY

**HS4**


(S220)

**HS5**

(S222)

**CAPACITIES**

MODEL	H.S.4	H.S.5
CODE	S220	S222
Plate	4mm(3/16")	5mm(7/32")
Flat	60mm x 5mm (2 3/8" x 7/32")	70mm x 6mm (2 3/4" x 1/4")
Round	11mm(7/16")	13mm (1/2")
Blade	155mm(6")	200mm
Cut Length	110mm(4 1/4")	160mm



## HAND PUNCH

(P114)

Includes 6 punches & dies

MAX. PUNCH CAP. IN MILD STEEL	
Dia.	Thickness
10 x	4mm
8 x	4mm
6 x	3mm
5 x	3mm
4 x	2mm
3 x	1.5mm

- 10mm in 4mm Plate capacity
- Throat depth 3" (75mm)
- Ideal for quick production work
- Punch & Dies: 3,4,5,6,8 & 10mm

