

Some items are subject to freight charges.  
All prices include GST. Plug & lead not supplied on 415 volt machines.  
Specifications & prices are subject to change without notice.



## HYDRAULIC NOTCHER HN-200x4mm

(S230)

- Hydraulically driven
- Constructed with steel welded plate, giving a rigid working platform
- 200 x 200mm MS capacity
- Max. notching thickness: 4mm MS
- Includes: squaring guides, scales, & angle gauge
- Remote foot pedal



## VARIABLE RAKE HYDRAULIC NOTCHER

### HKA-200x4mm HKA-200x6mm

(S234)

(S236)

- 30° - 140° Notching angle, easily set by two handles
- Rigidly constructed lower frame, work table, and cutting beam
- Automatic blade gap adjustment for all sheet thicknesses
- Engraved squaring guides, scales, and angle gauge
- Self-lubricating, precision guides for a burr-free cutting quality
- Extended work table with t-slots
- Safe, durable, and easy operation with footswitches
- Scrap-collection drawer
- Maintenance-free hydraulics



## VERTICAL GEARED SLOTING MACHINE

### SL-250

(S702)

### SL-300

(S703)

#### SPECIFICATIONS

MODEL	SL-250	SL-300
CODE	S702	S703
SIZE STROKE	250 (10")	300 (12")
RAM STROKE PER MINUTE	26-36	26-36
THROAT DEPTH	350	400
ROTARY TABLE SIZE (mm)	375	500
CHUCK SIZE (mm)	250	315
MOTOR (HP/Voltage)	2HP/415V	3HP/415V
WEIGHT(kg)	1000	1500

#### FEATURES

- Heavy duty cast iron construction
- Adjustable stroke
- Includes rotary table and chuck



SL-250

## PB-820 PANBRAKE

### 2440 x 2mm cap

(S564)

#### FEATURES

- Removable fingers
- Heavy duty steel fabricated construction
- Made in China



PB-820



(Cutters not included)



(T8533)

### PICCOLO SET

- 12mm-40mm Core Drill Capacity
- 1000 Watt Motor
- 400 RPM
- 9000N Magnetic Adhesion
- 50mm Core Drill Cutting Depth
- 132mm Stroke
- 100-200mm Height Adjustment
- Rota Quick-Change System
- Integrated Coolant System
- Solid Brass Guides
- Durable Keyboard
- Safety Belt
- Plastic Transport Case



(T8510)

## PORTABLE MAGNETIC DRILLING UNITS

### NEW GEN50 RQ

- 12mm-50mm Core Drill Capacity
- 1200 Watt Motor
- 2 Speed Gearbox 250/400 RPM
- 16000N Magnetic Adhesion
- 50mm Core Drill Cutting Depth
- 170mm Stroke
- 100-250mm Height Adjustment
- Rota Quick-Change System
- Integrated Coolant System
- Solid Brass Guides
- Durable Keyboard
- Safety Belt
- Plastic Transport Case



(T8621)

### JUNIOR TAPER

- Up to 60mm Core Drill Capacity
- 1000 Watt Motor
- 4 Speed Gearbox 110/175/245/385 RPM
- Gearbox with Clutch
- 20000N 3 Coil Magnetic Adhesion
- Up to 110mm Core Drill Cutting Depth
- 200mm Stroke
- 225-280mm Height Adjustment
- No.3 Morse Taper
- Adjustable Foot 30Deg Left/Right
- Solid Brass Guides
- Safety Belt
- Plastic Transport Case
- Optional Extras:  
Coolant Unit and Core Drill Holder



(T8630)

### MASTER TAPER

- Over 100mm Core Drill Capacity
- 1000 Watt Motor
- 4 Speed Gearbox 110/175/245/385 RPM
- Gearbox with Clutch
- 20000N 3 Coil Magnetic Adhesion
- Up to 110mm Core Drill Cutting Depth
- 245mm Stroke
- 225-400mm Height Adjustment
- No.3 Morse Taper
- Adjustable Foot 30Deg Left/Right
- Solid Brass Guides
- Safety Belt
- Plastic Transport Case
- Optional Extras:  
Coolant Unit and Core Drill Holder

