

Some items are subject to freight charges.
 All prices include GST. Plug & lead not supplied on 415 volt machines.
 Specifications & prices are subject to change without notice.

HAFCO METALMASTER BENCH LATHES

AL-30 (L194) 180mm x 300mm


FEATURES:

- Precision 'V'-beds are hardened and ground
- Cast Iron ribbed bed
- Dovetailed cross and compound slides
- Electric variable speed 0 to 2500rpm
- Includes a full set of change gears for metric thread cutting
- Standard accessories included: 3-jaw chuck with reversible jaws, chip tray & rear splash guard
- Ideal for the hobbyist
- Includes 8mm, 5 piece Turning Tool Set

* Optional Accessories

- 80mm 4 Jaw Chuck (L195)
- 160mm Face Plate (L196)
- 1xTravelling & 1xFixed Steady (L197)

SPECIAL PACKAGE PRICE



AL-50GB (L158) 230mm x 500mm

FEATURES:

- Precision 'V'-beds are hardened and ground
- Cast iron ribbed bed
- Dovetailed cross and compound slides
- Adjustable ball bearings spindle
- 6 spindle speeds from 100 to 1800rpm
- Metric calibration
- Norton style - quick change gearbox
- Metric & Imperial thread cutting

QUICK-CHANGE GEARBOX

OPTIONAL STAND



AL50GB PRICE INCLUDES:
 3-jaw chuck with reverse jaws, 4-jaw chuck, faceplate, steadies, change gears, dead centre, thread-cutting dial, rear splash guard & drip tray, spanners, toolbox, & instruction booklet

OPTIONAL ACCESSORIES



Quick Change Toolpost
- see Pg37

FITTING & MACHINING BOOK

- Hardcover
- 640 pages



Tool Sets
- see Pg35



SPECIFICATIONS

| MODEL | AL-30 | AL-50GB |
|--------------------------|---------------------|----------------|
| CODE | L194 | L158 |
| TOOLS TO SUIT | 8mm | 12mm |
| CENTRE HEIGHT | 90mm | 115mm |
| DISTANCE BETWEEN CENTRES | 300mm | 500mm |
| SWING OVER BED | 180mm | 220mm |
| SWING OVER CROSS-SLIDE | 112mm | 130mm |
| SPINDLE BORE | 20mm | 20mm |
| TAILSTOCK TAPER | 2MT | 2MT |
| SPINDLE SPEED RANGES | Variable(0-2500rpm) | 6(100-1800rpm) |
| LEADSCREW | Metric | Metric |
| IMPERIAL THREAD RANGE | No | 8 - 56TPI |
| METRIC THREAD RANGE | 0.4 - 2.0mm | 0.5 - 3.0mm |
| MOTOR | 250W/240V | 550W/240V |
| WEIGHT (kg) | 40kg | 99kg |

