

Bench & Pedestal Drilling Machines



Micro-Switch on Pulley Guard



Tilting Cast Iron Table



Drilling depth stop setting



Emergency Stop Switch



Key Lockable Switch



Emergency Stop Switch



Bench with Cabinet Stand



Pedestal

Features:

- Quiet V-belt drive system with 3MT spindle
- Quick action V-belt tensioning lever
- Safety magnetic-type switch
- Rack & pinion table height adjustment with locking lever
- Heavy duty chuck guard with micro switch
- Thick walled column ensuring greater rigidity
- Double locking table tilts left & right to 45° & rotates 360°
- Drilling depth stop setting with scale
- T-slotted work table
- 0.75kW / 1hp 240V fan-cooled motor
- Large spindle diameters and heavy castings
- Safety cut out switch on belt guard
- Includes heavy duty cabinet stand (Bench model only)

Fitted with Additional Safety Electrics:

- Micro out out switch fitted to belt cover
- Keyed lockable isolation switch
- Raised red (DOL) emergency stop switch
- Test and tag certificate on 240V lead

Includes:

- 125mm precision drill vice
- 13mm keyless drill chuck
- 3MT x JT6 Drill chuck arbor
- 2-1MT sleeve
- 3-2MT sleeve
- M10 x 12mm Tee nuts



ITEM No.		3A / 3B	2A / 2B
ORDER CODE		K8201 / K8202	K8200 / K8204
MODEL		PD-35	PD-35
BENCH/PEDESTAL	Type	Bench	Pedestal
DRILL CAPACITY	mm	31.5	31.5
SPINDLE TAPER	MT	3	3
SPINDLE TRAVEL	mm	125	125
THROAT DEPTH	mm	225	225
QUILL DIAMETER	mm	72	72
COLLAR DIAMETER	mm	92	92
COLUMN DIAMETER	mm	92	92
SPINDLE TO TABLE (MAX)	mm	330	730
SPINDLE TO BASE (MAX)	mm	775	1175
TABLE TYPE	O / □	□	□
TABLE SIZE	mm	350 x 350	350 x 350
DRIVE BELT TYPE	Section	B	B
SPINDLE STEPS	No.	9	9
SPINDLE SPEEDS	rpm	190-1690	190-1690
MOTOR POWER	kW / hp	0.75 / 1	0.75 / 1
MOTOR VOLTAGE	V	240 / 415	240 / 415
DIMENSIONS (LxWxH)	cm	18 x 20 x 135	18 x 20 x 135
WEIGHT (Nett)	kg	136	136

