

Some items are subject to freight charges.

All prices include GST. Plug & lead not supplied on 415 volt machines. Specifications & prices are subject to change without notice.



Doosan Infracore

# VERTICAL MACHINING CENTRES

*Mynx Series*

## NM 410/510



- Fast 1.5 second tool change with Cam type ATC (opt.)
- Powerful 15kW high torque spindle motor
- High speed 8000 or 12000rpm spindle
- Axis rapid traverse 36m/min
- Large diameter double pretensioned ballscrews
- Compact design with swivelling pendant control and remote MPG
- Fanuc Oi-M control

## Mynx 540/650/750



- Fast 1.5 second tool change with Cam type ATC (opt.)
- Powerful 22kW(750) high torque spindle motor
- High speed 8000/12000rpm spindle
- Solid box way construction
- Axis rapid traverse up to 30m/min(540)
- Large diameter double pretensioned ballscrews
- Compact design with swivelling pendant control and remote MPG
- Fanuc 21i-M control
- ALSO AVAILABLE IN BT50 TAPER

**LARGER MODELS AVAILABLE**

**SPECIFICATIONS**

MODEL	MYNX 410/510	MYNX 540/650/750
STROKE X-AXIS(mm)	762/1020	1020/1300/1525
STROKE Y-AXIS(mm)	410/510	510/650/762
STROKE Z-AXIS(mm)	510/625	625
TABLE SIZE(mm)	920 x 430/1200 x 500	1200 x 500/1400 x 650/1600 x 750
ALLOWABLE TABLE LOAD(kg)	600/800	800/1000/1500
TOOL SHANK	BT40	BT40 (BT50 opt.)
TOOL STORAGE CAPACITY	24{cam24 / 30}	24/24(30 OPT.)/24 / 30
SPINDLE SPEEDS(rpm)	8000(12000 OPT.)	8000(12000 OPT.)/8000(12000 OPT.)/12000
RAPID TRAVERSE(X/Y/Z m/min)	36/36/32 / 36/36/30	30/30/24
SPINDLE MOTOR(kW)	15	15, 15, 22/26
WEIGHT(kg)	5000/6500	7000/8500/13500



**General Tools (Adelaide) Pty Ltd** Phone +618 8262 6199 Fax +618 8262 6044  
 7 Newcastle Crescent, Cavan, South Australia 5094  
 E generaltools@bigpond.com [www.generaltools.com.au](http://www.generaltools.com.au)